

NEW

■ GEBERIT

THE NEW GEBERIT DUOFIX



**KNOW
HOW**
INSTALLED

DISCOVER THE NEW DUOFIX

FOR ANY INSTALLATION SITUATION

- 1



PULL-OUT SIDE FASTENING PLATE
Pull-out side fastening on the upper frame end for mounting on vertical studs for room-height applications.
- 2



ALTERNATE POSITION FOR WALL ANCHORS
An additional fastening hole for wall anchors to adjust their position to suit the structural conditions, e.g. in the case of obstacles or cables behind the wall.
- 3




SUITABLE FOR 25 CM HIGH FLOOR CONSTRUCTION
Extendible leg supports with a larger adjustable range for floor constructions up to 25 cm.
- 4




CLEVER FOOT PLATE DESIGN
Thanks to a hollow space, the foot plate can also be mounted above the fastening screws on the floor profile without the screw head getting in the way.

OPTIMISED HYDRAULICS

- 5



HIGH PERFORMANCE FLUSH VALVE
The Geberit flush valve delivers reliable performance and easy maintenance in concealed cisterns, backed by decades of proven durability.
- 6



QUIET INLET VALVE
The Type 383 inlet valve ensures consistent, quick filling with minimal noise emissions.



EASY HANDLING

- 7



ADDITIONAL MARKINGS
Markings on the blue frame make measuring easier for the centre of the threaded rod and middle of the connection bend.
- 8



SCREWS WITH HEXALOBULAR SOCKET
Screws with an additional hexalobular socket (TX) offer an additional choice of tool when working with a cordless screwdriver.
- 9



SIMPLE ADJUSTABLE PIPE BRACKET
The pipe bracket can be easily adjusted to suit the position of connection bend by sliding to ensure tension-free installation of the connection bend.

CO₂ REDUCTION

Thanks to a sophisticated design, the deployment of less material and the use of green electricity in production, each new Duofix element for wall-hung toilets results 10% fewer CO₂ emissions compared to its predecessor.



DEVELOPED WITH LOVE FOR DETAIL



Geberit has over 60 years of experience in concealed technology, with the Geberit Duofix element installed millions of times in the decades since. Geberit continues to develop the tried-and-tested Duofix element with a love for the finer details. This process incorporates both suggestions from plumbers and the latest findings from hydraulics and installation technology.

This means our customers always receive optimal flush technology – for today and tomorrow.

All dimensions and technical details remain unchanged, ensuring seamless compatibility and confident installation.



CURRENT MODEL: DUOFIX (Transition to Duofix 4 in early 2026)
 → 111.698.00.1
 Geberit Duofix element for wall-hung toilet, 114 cm, with Sigma8 concealed cistern 4.5/3L
 →111.697.00.1
 Geberit Duofix element for wall-hung toilet, 114cm, with Sigma8 concealed cistern 6/3L



NEW: DUOFIX 4 (Available in Early 2026)
 → 111.698.00.2
 Geberit Duofix element for wall-hung toilet, 114 cm, with Sigma8 concealed cistern 4.5/3L
 → 111.697.00.2
 Geberit Duofix element for wall-hung toilet, 114cm, with Sigma8 concealed cistern 6/3L

Current Duofix available during transition to Duofix 4 (early 2026). No immediate changes required, existing installation remains compatible.

50 YEARS OF
SPARE PARTS
AVAILABILITY



15 YEAR
WARRANTY

>60 YEARS OF
CONCEALED
TECHNOLOGY

The warranty terms can be found at www.geberit.com.au

Geberit Pty Ltd
Unit 1 & 6, 13 Boundary Road
Northmead, NSW 2152
Australia

P 02 9889 7866
sales.au@geberit.com

www.geberit.com.au